



## IMPACT(TM) Heavy-Duty Specifications

<b>Imperial</b>	<b>V-Plow</b>	<b>Straight Blade</b>
Moldboard Options	Steel	Steel
Blade Type	V-Plow	Straight Blade
Vehicle Compatibility	Full Sized UTVs & Series 1 Tractors	Full Sized UTVs & Series 1 Tractors
Approx. Weight* (Without Mount)	355 lb	261 lb
Plowing Width** (Full Angle)	Full Angle: 5'0" Scoop: 4'7" Full V: 5'0"	Full Angle: 5'4"
Blade Width	6'0"	6'0"
Blade Height	At Center: 25.75" At End: 29.25"	23.5"
Blade Thickness	14 ga	14 ga
Trip Springs	2	2
Ribs	6	4
Lift Cylinder	1.5" x 6"	1.5" x 6"
Angling Rams	1" x 8.75"	1" x 7"
Cutting Edge	¼" x 5"	¼" x 5"

<b>Metric</b>	<b>V-Plow</b>	<b>Straight Blade</b>
Models	V-Plow	Straight Blade
Moldboard Options	Steel	Steel
Blade Type	V-Plow	Straight Blade
Vehicle Compatibility	Full Sized UTVs & Series 1 Tractors	Full Sized UTVs & Series 1 Tractors
Approx. Weight*(Without Mount)	161 kg	118 kg
Plowing Width** (Full Angle)	Full Angle: 1.5 m Scoop: 1.4 m Full V: 1.5 m	Full Angle: 1.6 m
Blade Width	1.83 m	1.83 m
Blade Height	At Center: 65.4 cm At End: 74.3 cm	59.7 cm
Blade Thickness	1.90 mm	1.90 mm
Trip Springs	2	2
Ribs	6	4
Lift Cylinder	3.8 cm x 15.2 cm	3.8 cm x 15.2 cm
Angling Rams	2.5 cm x 22.2 cm	2.5 cm x 17.8 cm
Cutting Edge	0.6 cm x 12.7 cm	0.6 cm x 12.7 cm

\*Does not include vehicle mount weight. Please refer to the Quick Match program for specific vehicle applications. \*\*IMPACT UTV V-Plow: For UTVs with a wider wheelbase, width can be adjusted to: Full Angle 5'6" (1.7 m), Scoop 5'5" (1.6 m), Full V 5'6" (1.7 m)