

ENFORCER™

DIMENSION

SPECIFICATION	97545	97540
BLADE WIDTH	7'6" Stainless Steel	7'6" Powder-Coated Steel
APPROX. WEIGHT Approximate weight does not include vehicle mount (additional weight range: 28 lb to 145 lb). Please refer to Quick Match for specific vehicle applications.	556 lbs	511 lbs
PLOWING WIDTH (FULL ANGLE)	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"
BLADE HEIGHT	At Center: 27" At End: 33"	At Center: 27" At End: 33"
BLADE THICKNESS	14 ga	14 ga
LIFT CYLINDER	1-1/4" x 8.625"	1-1/4" x 8.625"
ANGLING RAMS	1-1/2" x 12"	1-1/2" x 12"
CUTTING EDGE	3/8" x 6" (Standard)	3/8" x 6" (Standard)

CONSTRUCTION

SPECIFICATION	97545	97540
MOLDBOARD OPTIONS	Stainless Steel	Powder-Coated Steel
BLADE TYPE	V-Plow	V-Plow
VEHICLE COMPATIBILITY	Half-Ton Trucks & Series 3 Tractors	Half-Ton Trucks & Series 3 Tractors
TRIP SPRINGS	2	2
RIBS	6	6
MOUNT TYPE	UltraMount® 2	UltraMount® 2