

PRO-PLOW® 3

DIMENSION

SPECIFICATION	93776	93773	93771	93768
BLADE WIDTH	7'6" Stainless Steel	7'6" Powder-Coated Steel	8' Stainless Steel	8' Powder-Coated Steel
APPROX. WEIGHT Approximate weight does not include vehicle mount (additional weight range: 28 lb to 145 lb). Please refer to Quick Match for specific vehicle applications.	598 lbs	581lbs	635 lbs	617 lbs
PLOWING WIDTH	79.5"	79.5"	84.8"	84.8"
BLADE HEIGHT	29"	29"	29"	29"
BLADE THICKNESS	14 ga	14 ga	14 ga	14 ga
LIFT CYLINDER (SINGLE ACTING) Lift Cylinder only available for hydraulic models.	1.5" x 8"	1.5" x 8"	1.5" x 8"	1.5" x 8"
CUTTING EDGE	3/8" x 6" (Standard)	3/8" x 6" (Standard)	3/8" x 6" (Standard)	3/8" x 6" (Standard)

CONSTRUCTION

SPECIFICATION	93776	93773	93771	93768
MOLDBOARD OPTIONS	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
BLADE TYPE	Straight Blade	Straight Blade	Straight Blade	Straight Blade
VEHICLE COMPATIBILITY	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors
TRIP SPRINGS	2	2	2	2
RIBS	8	8	8	8
ANGLING RAMS (SINGLE-ACTING)	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"
MOUNT TYPE	UltraMount® 2	UltraMount® 2	UltraMount 2	UltraMount 2