

Tri-Shield

DIMENSION

SPECIFICATION	85695	93265-1	93270	93275
CAPACITY	50 Gallons	50 Gallons	200 Gallons	100 Gallons Expansion
SPREADER COMPATIBILITY	MARAUDER S070A / S070C	MARAUDER S150A / S150C S220A / S220C P150A / P150C P220A / P220C MARAUDER S150A / S150C S220A / S220C P150A / P150C P220A / P220C	MARAUDER S300A / S300C S400A / S400C S500A / S500C	MARAUDER S300A / S300C S400A / S400C S500A / S500C
OVERALL DIMENSIONS (LXWXH)	64" x 60" x 26"	64" x 60" x 26"	64" x 72" x 36"	26" x 72" x 28"
TANK DIMENSIONS (LXWXH)	26" x 60" x 23"	26" x 60" x 23"	58" x 72" x 23"	26" x 72" x 28"

CONSTRUCTION

SPECIFICATION	85695	93265-1	93270	93275
TANKS	Two 25 Gallon Tanks	Two 25 Gallon Tanks	Four 50 Gallon Tanks	Two 50 Gallon Tanks
MOTOR/PUMP	12v Motor 7 Gallon Per Minute (Pump Capacity) 2.5 Gallon Per Minute (System Output) 12v Motor	12v Motor 7 Gallon Per Minute (Pump Capacity) 5 Gallon Per Minute (System Output) 12v Motor	12v Motor 7 Gallon Per Minute (Pump Capacity) 5 Gallon Per Minute (System Output) 12v Motor	-
WIRING HARNESS	Loomed, Molded Plugs	Loomed, Molded Plugs	Loomed, Molded Plugs	-
CONTROL	Integrated, In-Cab On/Off	Integrated, In-Cab On/Off	Integrated, In-Cab On/Off	-
MOUNTING	Nested With Hopper	Nested With Hopper	Nested With Hopper	Nested With Hopper