SPECIFICATIONS · IMPERIAL

PRO PLUS®

DIMENSION

SPECIFICATION	76980	76974	76901
BLADE WIDTH	8'	8'6"	9'
APPROX. WEIGHT Approximate weight does not include vehicle mount (additional weight range: 28 lb to 145 lb). Please refer to Quick Match for specific vehicle applications.	823 lbs	840 lbs	858 lbs
PLOWING WIDTH (FULL ANGLE)	6'11"	7'4"	7'9"
BLADE HEIGHT	31.5"	31.5"	31.5"
BLADE THICKNESS	12 ga	12 ga	12 ga
LIFT CYLINDER	1-1/2" x 8"	1-1/2" x 8"	1-1/2" x 8"
ANGLING RAMS	1-1/2" x 12"	1-1/2" x 12"	1-1/2" x 12"
CUTTING EDGE	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)

CONSTRUCTION

SPECIFICATION	76980	76974	76901
MOLDBOARD OPTIONS	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel
BLADE TYPE	Straight Blade	Straight Blade	Straight Blade
VEHICLE COMPATIBILITY	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (50 to 70 HP) & Tractors
SHOCK ABSORBERS	2	2	2
TRIP SPRINGS	4	4	4
RIBS	8	8	8
MOUNT TYPE	UltraMount® 2	UltraMount 2	UltraMount 2