

MVP 3™

DIMENSION

SPECIFICATION	74485	74685	74585	74495	74695	74595	74499	74699
BLADE WIDTH	8'6"	8'6"	8'6"	9'6"	9'6"	9'6"	10'6"	10'6"
APPROX. WEIGHT Approximate weight does not include vehicle mount (additional weight range: 28 lb to 145 lb). Please refer to Quick Match for specific vehicle applications.	988 lbs	988 lbs	943 lbs	1,070 lbs	1,070 lbs	1,013 lbs	1,301 lbs	1,301 lbs
PLOWING WIDTH (FULL ANGLE)	Full Angle: 7'5" Scoop: 7'2" Full V: 7'8"	Full Angle: 7'5" Scoop: 7'2" Full V: 7'8"	Full Angle: 7'5" Scoop: 7'2" Full V: 7'8"	Full Angle: 8'6" Scoop: 8'2" Full V: 8'7"	Full Angle: 8'6" Scoop: 8'2" Full V: 8'7"	Full Angle: 8'6" Scoop: 8'2" Full V: 8'7"	Full Angle: 9'9" Scoop: 9'7" Full V: 9'11"	Full Angle: 9'9" Scoop: 9'7" Full V: 9'11"
BLADE HEIGHT	At Center: 31" At End: 38"	At Center: 31" At End: 38"	At Center: 31" At End: 38"	At Center: 31" At End: 39"	At Center: 31" At End: 39"	At Center: 31" At End: 39"	At Center: 35" At End: 45"	At Center: 35" At End: 45"
BLADE THICKNESS	14 ga	14 ga	0.25"	14 ga	14 ga	0.25"	11 ga	12 ga
LIFT CYLINDER	1-3/4" x 8"	1-3/4" x 8"	1-3/4" x 8"	1-3/4" x 8"	1-3/4" x 8"	1-3/4" x 8"	1-3/4" x 8"	1-3/4" x 8"
ANGLING RAMS	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"	1-3/4" x 11"	2" x 11"	2" x 11"
CUTTING EDGE	3/8" x 6" (Standard)	3/8" x 6" (Standard)	3/8" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)

CONSTRUCTION

SPECIFICATION	74485	74685	74585	74495	74695	74595	74499	74699
MOLDBOARD OPTIONS	Powder-Coated Steel	Stainless Steel	Poly	Powder-Coated Steel	Stainless Steel	Poly	Powder-Coated Steel	Stainless Steel
BLADE TYPE	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow	V-Plow
VEHICLE COMPATIBILITY	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 7 (under 27,500 lb GVWR)	Truck Class 2 - 7 (under 27,500 lb GVWR)
TRIP SPRINGS	4	4	4	6	6	6	6	6
RIBS	8	8	8	8	8	8	8	8
MOUNT TYPE	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount 2	UltraMount 2	UltraMount 2	UltraMount 2	UltraMount 2