

WIDE-OUT™ & WIDE-OUT™ XL

DIMENSION

SPECIFICATION	85810-1	85850-1
BLADE WIDTH	8'-10' (#180210-higher)	8'6"-11'
APPROX. WEIGHT Approximate weight does not include vehicle mount (additional weight range: 28 lb to 145 lb). Please refer to Quick Match for specific vehicle applications.	1,057 lbs	1,120 lbs
PLOWING WIDTH (FULL ANGLE)	Retracted: 7'2" Expanded: 9' Scoop: 7'11"	Retracted: 7'11" Expanded: 10'6" Scoop: 9'6"
BLADE SIZE	Retracted: 8' Expanded: 10' Scoop: 8'10"	Retracted: 8'6" Expanded: 11' Scoop: 9'10"
BLADE HEIGHT	At Center: 31" At End: 35"	At Center: 31" At End: 36"
BLADE THICKNESS	14 ga	14 ga
LIFT CYLINDER	1-3/4" x 8"	1-3/4" x 8"

CONSTRUCTION

SPECIFICATION	85810-1	85850-1
MOLDBOARD OPTIONS	Powder-Coated Steel	Powder-Coated Steel
BLADE TYPE	Adjustable Winged Blade	Adjustable Winged Blade
VEHICLE COMPATIBILITY	Truck Class 2 - 5 & Tractors	Truck Class 2 - 6
TRIP SPRINGS	4	4
RIBS	6	8
ANGLING RAMS	1-1/2" x 10"	1-1/2" x 10"
CUTTING EDGE	1/2" x 6" (Standard)	1/2" x 6" (Standard)
MOUNT TYPE	UltraMount® 2	UltraMount 2