

PRO-PLOW 3

Imperial	93776	93773	93771	93768
Blade Width	7'6"	7'6"	8'	8'
Moldboard Options	Stainless Steel	Powder-Coated	Stainless Steel	Powder-Coated
Blade Type	Straight Blade	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors
Approx. Weight* (Without Mount)	Stainless: 598 lbs	Powder-Coated: 581lbs	Stainless: 635 lbs	Powder-Coated: 617 lbs
Plowing Width (at 28-degrees)	79.5"	79.5"	84.8"	84.8"
Blade Height	29"	29"	29"	29"
Blade Thickness	14 ga	14 ga	14 ga	14 ga
Trip Springs	2	2	2	2
Ribs	8	8	8	8
Lift Cylinder (Single-Acting)	1.5" x 8"	1.5" x 8"	1.5" x 8"	1.5" x 8"
Angling Rams (Single-Acting)	1.5" x 10"	1.5" x 10"	1.5" x 10"	1.5" x 10"
Cutting Edge	3/8 " x 6" (Standard)	3/8 " x 6" (Standard)	3/8 " x 6" (Standard)	3/8 " x 6" (Standard)
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount 2	UltraMount 2

Metric	93776	93773	93771	93768
Models	93776	93773	93771	93768
Blade Width	2.29 m	2.29 m	2.44 m	2.44 m
Moldboard Options	Stainless Steel	Powder-Coated	Stainless Steel	Powder-Coated
Blade Type	Straight Blade	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors	Truck Class 2 - 3 & Tractors
Approx. Weight* (Without Mount)	Stainless: 271 kg	Powder-Coated: 264 kg	Stainless: 288 kg	Powder-Coated: 280 kg
Plowing Width (at 28-degrees)	201.9 cm	201.9 cm	215.4 cm	215.4 cm
Blade Height	73.66 cm	73.66 cm	73.66 cm	73.66 cm
Blade Thickness	14 ga	14 ga	14 ga	14 ga
Trip Springs	2	2	2	2
Ribs	8	8	8	8
Lift Cylinder (Single-Acting)	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm
Angling Rams (Single-Acting)	3.81 cm x 25.4 cm	3.81 cm x 25.4 cm	3.81 cm x 25.4 cm	3.81 cm x 25.4 cm
Cutting Edge	0.95 cm x 15.24 cm (Standard)	0.95 cm x 15.24 cm (Standard)	0.95 cm x 15.24 cm (Standard)	0.95 cm x 15.24 cm (Standard)
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount 2	UltraMount 2

**Does not include vehicle mount (28 lb to 145 lb weight range). Please refer to the Quick Match program for specific vehicle*

PRO-PLOW 3

applications.