



Drop 250 & 600 Specifications

Imperial	250	600
Vehicle Compatibility*	UTVs, Compact Tractors & Wheel Loaders	UTVs, Compact Tractors & Wheel Loaders
Material Compatibility*	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes
Capacity (Weight)	350 lb	650 lb
Spreading Width	30" to 36"	30" to 36"
Approx. Weight (Empty)	130 lb	160 lb
Hopper Dimensions (LxWxH)	13" x 36.5" x 17.25"	17" x 36.5" x 28"
Dimensions Overall (LxWxH)	17" x 42" x 17.5"	20" x 42" x 28"
Hopper Construction	201 Stainless Steel	201 Stainless Steel
Capacity (Volume)	2.5 cu ft	6.0 cu ft
Motor	1/3 hp	1/3 hp
Frame, Hopper & Auger Drive Assembly	201 Stainless Steel	201 Stainless Steel
Available Mounts	3-Point Hitch, 2" Hitch Receiver, or In-Bed Mount	3-Point Hitch, 2" Hitch Receiver, or In-Bed Mount

Metric	250	600
Models	250	600
Vehicle Compatibility*	UTVs, Compact Tractors & Wheel Loaders	UTVs, Compact Tractors & Wheel Loaders
Material Compatibility*	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes	Salt, Sand, Salt/Sand Mix, Calcium Chloride Pellets & Calcium Flakes
Capacity (Weight)	158.8 kg	294.8 kg
Spreading Width	76.2 cm to 91.4 cm	76.2 cm to 91.4 cm
Approx. Weight (Empty)	59 kg	72.6 kg
Hopper Dimensions (LxWxH)	33 cm x 92.7 cm x 43.8 cm	43.2 cm x 92.7 cm x 71.1 cm
Dimensions Overall (LxWxH)	43.2 cm x 106.7 cm x 44.5 cm	50.8 cm x 106.7 cm x 71.1 cm
Hopper Construction	201 Stainless Steel	201 Stainless Steel
Capacity (Volume)	0.1 cu m	0.2 cu m
Motor	1/3 hp	1/3 hp
Frame, Hopper & Auger Drive Assembly	201 Stainless Steel	201 Stainless Steel
Available Mounts	3-Point Hitch, 2" Hitch Receiver, or In-Bed Mount	3-Point Hitch, 2" Hitch Receiver, or In-Bed Mount

* When choosing a spreader, follow weight capacity guidelines for the intended application.

** When spreading sand, an additional vibrator is required.