

## ENFORCER(TM) Specifications

<b>Imperial</b>	<b>97545</b>	<b>97540</b>
Blade Width	7'6"	7'6"
Moldboard Options	Stainless Steel	Powder-Coated Steel
Blade Type	V-Plow	V-Plow
Vehicle Compatibility	Half-Ton Trucks & Series 3 Tractors	Half-Ton Trucks & Series 3 Tractors
Approx. Weight* (Without Mount)	Stainless Steel: 556 lbs	Powder Coated: 511 lbs
Plowing Width (Full Angle)	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"	Full Angle: 6'7" Scoop: 6'5" Full V: 6'9"
Blade Height	At Center: 27" At End: 33"	At Center: 27" At End: 33"
Blade Thickness	Stainless Steel: 14 ga	Stainless Steel: 14 ga
Trip Springs	2	2
Ribs	6	6
Lift Cylinder	1 1/4" x 8.625"	1 1/4" x 8.625"
Angling Rams	1 1/2" x 12"	1 1/2" x 12"
Cutting Edge	0.375" x 6" (Standard)	0.375" x 6" (Standard)
Mount Type	UltraMount® 2	UltraMount® 2

<b>Metric</b>	<b>97545</b>	<b>97540</b>
Models	97545	97540
Blade Width	2.29 m	2.29 m
Moldboard Options	Stainless Steel	Powder-Coated Steel
Blade Type	V-Plow	V-Plow
Vehicle Compatibility	Half-Ton Trucks & Series 3 Tractors	Half-Ton Trucks & Series 3 Tractors
Approx. Weight* (Without Mount)	Stainless Steel: 252 kg	Powder Coated: 231 kg
Plowing Width (Full Angle)	Full Angle: 2.01 m Scoop: 1.96 m Full V: 2.06 m	Full Angle: 2.01 m Scoop: 1.96 m Full V: 2.06 m
Blade Height	At Center: 68.58 cm At End: 83.82 cm	At Center: 68.58 cm At End: 83.82 cm
Blade Thickness	Stainless Steel: 14 ga	Stainless Steel: 14 ga
Trip Springs	2	2
Ribs	6	6
Lift Cylinder	3.18 cm x 21.91 cm	3.18 cm x 21.91 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Cutting Edge	0.95 cm x 15.24 cm (Standard)	0.95 cm x 15.24 cm (Standard)
Mount Type	UltraMount® 2	UltraMount® 2

\* Does not include vehicle mount (28 lb to 145 lb weight range). Please refer to the Quick Match program for specific vehicle applications.