

IMPACT(TM) Mid-Duty UTV Plow Specifications

Imperial	<i>5'6</i> "	<i>6'0"</i>
Moldboard Options	High-Strength Steel	High-Strength Steel
Blade Type	Straight Blade	Straight Blade
Vehicle Compatibility	Mid Sized, Crossover & Sport UTVs	Mid Sized, Crossover & Sport UTVs
Approx. Weight* (Without Mount)	Hydraulic: 190 lb Winch: 175 lb	Hydraulic: 195 lbWinch: 180 lb
Plowing Width (Full Angle)	4'11"	5'4"
Blade Width	5'6"	6'0"
Blade Height	19.67"	19.67"
Blade Thickness	16 ga	16 ga
Trip Springs	2	2
Ribs	4	4
Lift Cylinder** (Single Acting)	Hydraulic: 1.5" x 3" (one)Winch: N/A	Hydraulic: 1.5" x 3" (one)Winch: N/A
Angling Rams**(Double Acting)	Hydraulic: 1.5" x 4"Winch: N/A	Hydraulic: 1.5" x 4"Winch: N/A
Cutting Edge	1⁄4" x 4"	1⁄4" x 4"
Mount Type	Mid-Duty UTV Mounting System	Mid-Duty UTV Mounting System

Metric	5'6"	6'0"
Models	5'6"	6'0"
Moldboard Options	High-Strength Steel	High-Strength Steel
Blade Type	Straight Blade	Straight Blade
Vehicle Compatibility	Mid Sized, Crossover & Sport UTVs	Mid Sized, Crossover & Sport UTVs
Approx. Weight* (Without Mount)	Hydraulic: 86.2 kgWinch: 79.4 kg	Hydraulic: 88.5 kgWinch: 81.7 kg
Plowing Width (Full Angle)	1.50 m	1.63 m
Blade Width	1.7 m	1.8 m
Blade Height	50 cm	50 cm
Blade Thickness	0.15 cm	0.15 cm
Trip Springs	2	2
Ribs	4	4
Lift Cylinder** (Single Acting)	Hydraulic: 3.8 cm x 7.6 cmWinch: N/A	Hydraulic: 3.8 cm x 7.6 cmWinch: N/A
Angling Rams** (Double Acting)	Hydraulic: 3.8 cm x 10.2 cmWinch: N/A	Hydraulic: 3.8 cm x 10.2 cmWinch: N/A
Cutting Edge	0.6 cm x 10.2 cm	0.6 cm x 10.2 cm
Mount Type	Mid-Duty UTV Mounting System	Mid-Duty UTV Mounting System

^{*}Does not include vehicle mount weight. Please refer to the Quick Match program for specific vehicle applications. **Lift Cylinder & amp; Angling Ram only available for hydraulic models.