

PRO-PLOW(R) Series 2 Specifications

Imperial	7'6"	8'	8'6"
Moldboard Options	Steel/Poly	Steel/Poly	Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3	Truck Class 2 & 3	Truck Class 2 & 3
Approx. Weight* (Without Mount)	Steel: 705 lbs Poly: 728 lbs	Steel: 720 lbs Poly: 740 lbs	738 lbs
Plowing Width (Full Angle)	6'6"	6'11"	7'4"
Blade Width	7'6"	8'	8'6"
Blade Height	29"	29"	29"
Blade Thickness	Steel: 11 ga Poly: 0.375"	Steel: 11 ga Poly: 0.375"	11 ga
Shock Absorbers	1	1	1
Trip Springs	4	4	4
Ribs	7	7	7
Lift Cylinder	1½" x 8"	1½" x 8"	1½" x 8"
Angling Rams	1½" x 10"	1½" x 10"	1½" x 10"
Cutting Edge	3/8" x 6" (Standard)	3/8" x 6" (Standard)	3/8" x 6" (Standard)
Mount Type	UltraMount® 2	UltraMount 2	UltraMount 2

Metric	7'6"	8'	8'6"
Models	7'6"	8'	8'6"
Moldboard Options	Steel/Poly	Steel/Poly	Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3	Truck Class 2 & 3	Truck Class 2 & 3
Approx. Weight* (Without Mount)	Steel: 319 kg Poly: 330 kg	Steel: 326 kg Poly: 335 kg	334 kg
Plowing Width (Full Angle)	1.98 m	2.11 m	2.24 m
Blade Width	2.29 m	2.44 m	2.59 m
Blade Height	73.66 cm	73.66 cm	73.66 cm
Blade Thickness	Steel: 11 ga Poly: 0.375"	Steel: 11 ga Poly: 0.375"	11 ga
Shock Absorbers	1	1	1
Trip Springs	4	4	4
Ribs	7	7	7
Lift Cylinder	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Cutting Edge	0.95 cm x 15.24 cm (Standard)	0.95 cm x 15.24 cm (Standard)	0.95 cm x 15.24 cm (Standard)
Mount Type	UltraMount® 2	UltraMount 2	UltraMount 2

*Does not include vehicle mount (28 lb to 145 lb weight range). Please refer to the Quick Match program for specific vehicle applications.