



PRO-PLOW(R) Series 2 Specifications

Imperial	7'6"	8'	8'6"
Moldboard Options	Steel/Poly	Steel/Poly	Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3	Truck Class 2 & 3	Truck Class 2 & 3
Approx. Weight* (Without Mount)	Steel: 653 lb Poly: 677 lb	Steel: 668 lb Poly: 690 lb	686 lb
Plowing Width (Full Angle)	6'6"	6'11"	7'4"
Blade Width	7'6"	8'	8'6"
Blade Height	29"	29"	29"
Blade Thickness	Steel: 11 ga Poly: 0.375"	Steel: 11 ga Poly: 0.375"	11 ga
Shock Absorbers	1	1	1
Trip Springs	4	4	4
Ribs	7	7	7
Lift Cylinder	1.5" x 8"	1.5" x 8"	1.5" x 8"
Angling Rams	1.5" x 10"	1.5" x 10"	1.5" x 10"
Cutting Edge	0.375" x 6"	0.375" x 6"	0.375" x 6"
Mount Type	UltraMount® 2	UltraMount 2	UltraMount 2

Metric	7'6"	8'	8'6"
Models	7'6"	8'	8'6"
Moldboard Options	Steel/Poly	Steel/Poly	Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3	Truck Class 2 & 3	Truck Class 2 & 3
Approx. Weight* (Without Mount)	Steel: 296.20 kg Poly: 307.08 kg	Steel: 303.00 kg Poly: 313.00 kg	311.16 kg
Plowing Width (Full Angle)	1.98 m	2.11 m	2.24 m
Blade Width	2.29 m	2.44 m	2.59 m
Blade Height	73.66 cm	73.66 cm	73.66 cm
Blade Thickness	Steel: 3.18 mm Poly: 9.52 mm	Steel: 3.18 mm Poly: 9.52 mm	3.18 mm
Shock Absorbers	1	1	1
Trip Springs	4	4	4
Ribs	7	7	7
Lift Cylinder	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Cutting Edge	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm
Mount Type	UltraMount® 2	UltraMount 2	UltraMount 2

*Does not include vehicle mount (28 lb to 145 lb weight range). Please refer to the Quick Match program for specific vehicle applications.