

PRO PLUS(R) Specifications

Imperial	76980	76974	76901
Blade Width	8'	8'6"	9'
Moldboard Options	Steel	Steel	Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (50 to 70 HP) & Tractors
Approx. Weight* (Without Mount)	823 lbs	840 lbs	858 lbs
Plowing Width (Full Angle)	6'11"	7'4"	7'9"
Blade Height	31.5"	31.5"	31.5"
Blade Thickness	12 ga	12 ga	12 ga
Shock Absorbers	2	2	2
Trip Springs	4	4	4
Ribs	8	8	8
Lift Cylinder	1½" x 8"	1½" x 8"	1½" x 8"
Angling Rams	1½" x 12"	1½" x 12"	1½" x 12"
Cutting Edge	½" x 6" (Standard)	½" x 6" (Standard)	½" x 6" (Standard)
Mount Type	UltraMount® 2	UltraMount 2	UltraMount 2

Metric	76980	76974	76901
Models	76980	76974	76901
Blade Width	2.44 m	2.59 m	2.74 m
Moldboard Options	Steel	Steel	Steel
Blade Type	Straight Blade	Straight Blade	Straight Blade
Vehicle Compatibility	Truck Class 2 & 3, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (Under 50 HP) & Tractors	Truck Class 2 - 5, Skid-Steers (50 to 70 HP) & Tractors
Approx. Weight* (Without Mount)	373 kg	381 kg	389 kg
Plowing Width (Full Angle)	2.11 m	2.24 m	2.36 m
Blade Height	80.01 cm	80.01 cm	80.01 cm
Blade Thickness	12 ga	12 ga	12 ga
Shock Absorbers	2	2	2
Trip Springs	4	4	4
Ribs	8	8	8
Lift Cylinder	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Cutting Edge	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)
Mount Type	UltraMount® 2	UltraMount 2	UltraMount 2

**Does not include vehicle mount (28 lb to 145 lb weight range). Please refer to the Quick Match program for specific vehicle applications.*