



Striker(R) (1.5-6.0 cu yd) Specifications

| Imperial | 1.5 cu yd | 2.0 cu yd | 3.0 cu yd | 4.5 cu yd (9') | 4.5 cu yd (10') | 6.0 cu yd |
|----------------------------|---|--|--|--|---|---|
| Vehicle Compatibility | 3/4- & 1-Ton Pickup Trucks | 3/4- & 1-Ton Pickup Trucks | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) |
| Material Compatibility | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand |
| Capacity | 1.5 cu yd | 2.0 cu yd | 3.0 cu yd | 4.5 cu yd | 4.5 cu yd | 6.0 cu yd |
| Spreading Width | Up to 40' | Up to 40' | Up to 40' | Up to 40' | Up to 40' | Up to 40' |
| Approx. Weight (Empty) | Dual 12V DC Sealed Motors <i>(595 lb)</i> | Dual 12V DC Sealed Motors <i>(615 lb)</i> Dual Hydraulic Motors <i>(615 lb)</i> | Dual 12V DC Sealed Motors <i>(695 lb)</i> Dual Hydraulic Motors <i>(695 lb)</i> | Dual 12V DC Sealed Motors <i>(815 lb)</i> Dual Hydraulic Motors <i>(815 lb)</i> | Dual Hydraulic Motors <i>(840 lb)</i> | Dual Hydraulic Motors <i>(885 lb)</i> |
| Overall Dimensions (LxWxH) | 105" x 50" x 51" | 117" x 50" x 51" | 129" x 50" x 70 ½" | 129" x 70" x 74 ¾" | 141" x 70" x 74 ¾" | 141" x 70" x 82 ¼" |
| Hopper Dimensions (LxWxH) | 84" x 50" x 33.25" | 96" x 50" x 33.25" | 108" x 50" x 40.75" | 108" x 70" x 45" | 119" x 70" x 45" | 119" x 70" x 52.5" |
| Body Side Length | 7' | 8' | 9' | 9' | 10' | 10' |
| Min. Bed Length | 62.5" | 74.5" | 91" | 91" | 102" | 102" |
| Conveyor Width | 16.5" | 16.5" | 16.5" | 16.5" | 16.5" | 16.5" |
| Spinner Size | 15.5" | 15.5" | 15.5" | 15.5" | 15.5" | 15.5" |
| Hopper Construction | 16 ga SS | 16 ga SS | 16 ga SS | 16 ga SS | 16 ga SS | 16 ga SS |

| Metric | 1.5 cu yd | 2.0 cu yd | 3.0 cu yd | 4.5 cu yd (9') | 4.5 cu yd (10') | 6.0 cu yd |
|------------------------|--------------------------------------|--------------------------------------|---|---|---|---|
| Models | 1.5 cu yd | 2.0 cu yd | 3.0 cu yd | 4.5 cu yd (9') | 4.5 cu yd (10') | 6.0 cu yd |
| Vehicle Compatibility | 3/4- & 1-Ton Pickup Trucks | 3/4- & 1-Ton Pickup Trucks | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) | Dump Body or Flatbed Trucks (Over 15,000 lb GVWR) |
| Material Compatibility | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand | Bulk Salt, 50/50 Salt/Sand Mix, Sand |
| Capacity | 1.15 cu m | 1.53 cu m | 2.29 cu m | 3.44 cu m | 3.44 cu m | 4.59 cu m |
| Spreading Width | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m | Up to 12.19 m |



Striker(R) (1.5-6.0 cu yd) Specifications

| | | | | | | |
|----------------------------|---|--|--|--|---|---|
| Approx. Weight (Empty) | Dual 12V DC Sealed Motors <i>(269.89 kg)</i> | Dual 12V DC Sealed Motors <i>(278.96 kg)</i> Dual Hydraulic Motors <i>(278.96 kg)</i> | Dual 12V DC Sealed Motors <i>(315.25 kg)</i> Dual Hydraulic Motors <i>(315.25 kg)</i> | Dual 12V DC Sealed Motors <i>(369.68 kg)</i> Dual Hydraulic Motors <i>(369.68 kg)</i> | Dual Hydraulic Motors <i>(381.02 kg)</i> | Dual Hydraulic Motors <i>(401.43 kg)</i> |
| Overall Dimensions (LxWxH) | 266.7 cm x 127 cm x 129.5 cm | 297.2 cm x 127 cm x 129.5 cm | 327.7 cm x 127 cm x 179.1 cm | 327.7 cm x 177.8 cm x 189.9 cm | 358.1 cm x 177.8 cm x 189.9 cm | 358.1 cm x 177.8 cm x 208.9 cm |
| Hopper Dimensions (LxWxH) | 213.4 cm x 127 cm x 84.5 cm | 243.8 cm x 127 cm x 84.5 cm | 274.3 cm x 127 cm x 103.5 cm | 274.3 cm x 177.8 cm x 114.3 cm | 302.3 cm x 177.8 cm x 114.3 cm | 302.3 cm x 177.8 cm x 133.4 cm |
| Body Side Length | 2.13 m | 2.44 m | 2.74 m | 2.74 m | 3.05 m | 3.05 m |
| Min. Bed Length | 158.8 cm | 189.2 cm | 231.1 cm | 231.1 cm | 259.1 cm | 259.1 cm |
| Conveyor Width | 42 cm | 42 cm | 42 cm | 42 cm | 42 cm | 42 cm |
| Spinner Size | 40 cm | 40 cm | 40 cm | 40 cm | 40 cm | 40 cm |
| Hopper Construction | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS | 1.5 mm SS |