



## WIDE-OUT(TM) & WIDE-OUT(TM) XL Specifications

<b>Imperial</b>	<b>8'-10' (#180210-higher)</b>	<b>8'6"-11'</b>
Moldboard Options	Steel	Steel
Blade Type	Winged Blade	Winged Blade
Vehicle Compatibility	Truck Class 2 - 5	Truck Class 2 - 5
Approx. Weight* (Without Mount)	1,057 lbs	1,120 lbs
Plowing Width (Full Angle)	Retracted: 7'2" Expanded: 9' Scoop: 7'11"	Retracted: 7'11" Expanded: 10'6" Scoop: 9'6"
Blade Width	Retracted: 8' Expanded: 10' Scoop: 8'10"	Retracted: 8'6" Expanded: 11' Scoop: 9'10"
Blade Height	At Center: 31" At End: 35"	At Center: 31" At End: 36"
Blade Thickness	14 ga	14 ga
Trip Springs	4	4
Ribs	6	8
Lift Cylinder	1 <sup>3</sup> / <sub>4</sub> " x 8"	1 <sup>3</sup> / <sub>4</sub> " x 8"
Angling Rams	1 <sup>1</sup> / <sub>2</sub> " x 10"	1 <sup>1</sup> / <sub>2</sub> " x 10"
Cutting Edge	1/2" x 6" (Standard)	1/2" x 6" (Standard)
Mount Type	UltraMount® 2	UltraMount 2

<b>Metric</b>	<b>8'-10' (#180210-higher)</b>	<b>8'6"-11'</b>
Models	8'-10' (#180210-higher)	8'6"-11'
Moldboard Options	Steel	Steel
Blade Type	Winged Blade	Winged Blade
Vehicle Compatibility	Truck Class 2 - 5	Truck Class 2 - 5
Approx. Weight* (Without Mount)	479 kg	507 kg
Plowing Width (Full Angle)	Retracted: 2.18 m Expanded: 2.74 m Scoop: 2.41 m	Retracted: 2.41 m Expanded: 3.20 m Scoop: 2.90 m
Blade Width	Retracted: 2.44 m Expanded: 3.05 m Scoop: 2.69 m	Retracted: 2.59 m Expanded: 3.35 m Scoop: 3.00 m
Blade Height	At Center: 78.74 cm At End: 88.90 cm	At Center: 78.74 cm At End: 91.44 cm
Blade Thickness	14 ga	14 ga
Trip Springs	4	4
Ribs	6	8
Lift Cylinder	4.45 cm x 20.32 cm	4.45 cm x 20.32 cm
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Cutting Edge	1.27 cm x 15.24 cm (Standard)	1.27 cm x 15.24 cm (Standard)
Mount Type	UltraMount® 2	UltraMount 2

*\*Does not include vehicle mount (28 lb to 145 lb weight range). Please refer to the Quick Match program for specific vehicle applications.*