

# ALL-NEW PILE DRIVER™ WITH TRACE™ EDGE TECHNOLOGY PUSHER PLOW

“



## GO BIG WITH SNOW REMOVAL.

When the snow starts falling, there's no time to waste. The world keeps moving, and the snow needs to get out of the way. With TRACE edge technology, the all-new PILE DRIVER pusher plows move massive amounts of snow—scraping down to the pavement—so you can get more jobs done faster. Available in 8', 10', 12', 14', and 16' widths, these pushers raise the bar on efficiency.



MORE JOBS. **DONE FASTER.**

# PILE DRIVER™ WITH TRACE™ EDGE TECHNOLOGY PUSHER PLOW



The all-new PILE DRIVER line up of pusher plows come in 8', 10', 12', 14', and 16' widths. Three heights and a common carrier attachment system make them compatible with skid loaders, wheel loaders, tractors, and backhoe loaders. The patent-pending TRACE edge technology allows the cutting edge to contour to the plowable surface for maximum snow removal. And they're backed by the best-in-class WESTERN® dealer network available for service and support.

## TRACE EDGE TECHNOLOGY

The terrain-response advanced cutting edge is comprised of independent, 2' sections that raise, oscillate, and trip to accommodate contours and obstacles in the plowable surface. Working together, the sections remove more snow, reducing the amount of salt required. Two greasing locations allow the operator to keep the components well lubricated for maximum performance.



RAISE



OSCILLATE



TRIP

## SELF-LEVELING SIDE PLATES WITH HEAVY-DUTY SHOES

The side plates with heavy-duty shoes self-level to ensure the TRACE edge remains in direct contact with the plowable surface. The shoes are easily replaceable to extend the life of the pusher.

## ¾" CUTTING EDGE WITH CARBIDE INSERTS

The PILE DRIVER plow performs in the most grueling commercial conditions. Each 2' section comes standard with a ¾" cutting edge with carbide insert and uses the same part number for easy replacement. No need to replace the full cutting edge, only the sections that show wear.

## COMMON ATTACHMENT PLATE

A common attachment plate with floating coupler makes installation easy with a wide variety of equipment and machinery, including skid-steers, wheel loaders, backhoes, and tractors. The floating coupler reduces negative down pressure from the vehicle, protecting against premature wear of the pusher cutting edge and components.



## EASY OPERATION

Operation of the PILE DRIVER plow is conveniently tied into the equipment's controls. Simply raise and lower the lift arm and angle the attachment plate to position the pusher in the correct orientation.

## SPECIFICATIONS

DIMENSIONS					OPERATIONAL				CONSTRUCTION				
BLADE WIDTH	BLADE HEIGHT	SIDE PLATE WIDTH	SIDE PLATE HEIGHT	MOLDBOARD RADIUS	CUTTING EDGE TECHNOLOGY	CUTTING EDGE MATERIAL	APPROX. SNOW CAPACITY	APPROX. WEIGHT*	MOUNT TYPE	MACHINE APPLICATION	VEHICLE HORSEPOWER COMPATIBILITY	WHEEL LOADER HORSEPOWER COMPATIBILITY	TRACTOR HORSEPOWER COMPATIBILITY
8' (2.44 m)	30" (76.2 cm)	56" (142.24 cm)	30" (76.2 cm)	27" (68.58 cm)	TRACE — Terrain Response Advanced Cutting Edge	High-carbon steel with carbide inserts	75 cu ft (2.14 cu m)	2127 lb (964.63 kg)	Skid-Steer	Skid-Steer	30–50 hp	—	—
10' (3.05 m)	30" (76.2 cm)	56" (142.24 cm)	30" (76.2 cm)	27" (68.58 cm)			94 cu ft (2.68 cu m)	2249 lb (1019.95 kg)	Skid-Steer	Skid-Steer	30–50 hp	—	—
8' (2.44 m)	36" (91.44 cm)	56" (142.24 cm)	36" (91.44 cm)	27" (68.58 cm)			108 cu ft (3.06 cu m)	2221 lb (1007.26 kg)	Skid-Steer / Coupler	Skid-Steer / Tractor / Wheel Loader	—	50–75 hp	50–100 hp
10' (3.05 m)	36" (91.44 cm)	56" (142.24 cm)	36" (91.44 cm)	27" (68.58 cm)			135 cu ft (3.82 cu m)	2377 lb (1078.00 kg)	Skid-Steer / Coupler	Skid-Steer / Tractor / Wheel Loader	—	50–75 hp	50–100 hp
12' (3.66 m)	42" (106.68 cm)	56" (142.24 cm)	42" (106.68 cm)	46" (116.84 cm)			219 cu ft (6.19 cu m)	2644 lb (1199.09 kg)	Coupler	Wheel Loader	—	100–125 hp	75–150 hp
14' (4.27 m)	42" (106.68 cm)	56" (142.24 cm)	42" (106.68 cm)	46" (116.84 cm)			TBD	2907 lb (1318.37 kg)	Coupler	Wheel Loader	—	100–125 hp	75–150 hp
16' (4.88 m)	42" (106.68 cm)	56" (142.24 cm)	42" (106.68 cm)	46" (116.84 cm)			TBD	3170 lb (1437.64 kg)	Coupler	Wheel Loader	—	100–125 hp	75–150 hp

\*Approximate weight is less mount

MORE JOBS. DONE FASTER.



Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. Other patents pending. Western Products offers a limited warranty for all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: PILE DRIVER, TRACE, WESTERN.



westernplows.com

Printed in U.S.A. | FORM NO. 31028-MA22

**DD** A DIVISION OF DOUGLAS DYNAMICS, LLC

Western Products | P.O. Box 245038 | Milwaukee, WI 53224-9538

©2022 Douglas Dynamics, LLC. All rights reserved.