

# ALL-NEW MARAUDER™

0.35 & 0.7 COMPACT STAINLESS STEEL HOPPERS



## RIGHT TOOL FOR THE JOB.

Based on the material your operation most commonly uses for de-icing, the WESTERN® MARAUDER line offers the best material delivery system for you. The S070A and S070C are suited for half-ton and light duty pickup trucks and the S035A and S035C are purpose-built for mid-duty UTVs and compact trucks.



### ALL-NEW HELIXX™ AUGER TECHNOLOGY

Patent-pending corkscrew material delivery system is optimized to operate in the target range for rock salt spreading best practices.

OR

### PINTLE CHAIN CONVEYOR

The large conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.

### RIVETED CONSTRUCTION

Constructed entirely of rivets and bolts, with no welding. Provides a cleaner stainless look and is easier to repair when service is needed.

### DUAL VARIABLE-SPEED CONTROL

Precisely match material delivery and spread patterns to conditions. Four accessory buttons and a dedicated blast button provide in-cab efficiency.

### FLIP-UP CHUTE

Provides convenient access to the hitch, better ground clearance, and easy clean-out.

### MARAUDER™ COMPACT STAINLESS STEEL HOPPERS



MARAUDER S070C shown



FLIP-UP CHUTE SHOWN

	S035A	S035C	S070A	S070C
Vehicle Compatibility	UTVS & Compact Trucks	UTVS & Compact Trucks	½-ton & Light Duty Pickup Trucks	½-ton & Light Duty Pickup Trucks
Material Compatibility	Bulk Salt	50/50 Salt/Sand Mix & Sand	Bulk Salt	50/50 Salt/Sand Mix & Sand
Capacity	0.35 cu yd. (0.27 cu m)		0.7 cu yd (0.54 cu m)	
Capacity – Weight*	750 lb (340.2 kg)		1,500 lb (680.39 kg)	
Spreading Width	Up to 30 feet (9.14 m)			
Approx. Weight – Empty	192 lb (87.1 kg)	235 lb (106.59 kg)	337 lb (152.9 kg)	420 lb (190.51 kg)
Overall Dimensions – LxWxH (cm)	52.75" x 38" x 45.5" (134 x 96.5 x 115.6)	57" x 38" x 46" (144.78 x 96.52 x 116.84)	81" x 42.75" x 45" (205.74 x 108.6 x 114.3)	81" x 43" x 46" (205.74 x 109.22 x 116.84)
Hopper Dimensions – LxWxH (cm)	30" x 38" x 25.75" (76.2x96.5x65.4)	30" x 38" x 26" (76.2 x 96.52 x 66.04)	54.5" x 42.75" x 27.25" (138.4 x 108.6 x 114.3)	54" x 43" x 28" (137.16 x 109.22 x 71.12)
Body Side Length	30" (0.76 m)	30" (0.76 m)	54" (1.37 m)	54" (1.37 m)
Minimum Bed Length Required	28.5" (72.4 cm)	30" (76.2 cm)	44" (111.8 cm)	44" (111.76 cm)
Conveyor Width	N/A	15.5" (39.21 cm)	N/A	15.5" (39.37 cm)
HELIXX Auger Technology	4" (10.2 cm) heavy-duty shaftless auger	N/A	4" (10.2 cm) heavy-duty shaftless auger	N/A
Spinner Size	12" (30.5 cm) diameter			
Hopper Construction	16 gauge stainless steel			

\* Material weight equates to approximately 2,160 lb/cu yd or 80 lb/cu ft (1 bag of rock salt)

### ACCESSORIES

50-gallon Pre-Wet & Direct Liquid Application Kit (S070A/S070C) | Extension Collars  
Central Point Grease Kit (S035C/S070C) | Spill Guard Kit | Tarp Kit | Inverted V Kit  
LED Strobe Light Kit | LED Work Light Kit | Vehicle-Side Harness Kit | Truck Upfit Kit  
Ratchet Tie-Down Kit

MORE JOBS. **DONE FASTER.**